



DX Baler Specifications and Dimensions

(800) 678-7320

sales@jv.com

Cram-A-Lot DX Series SPECIFICATIONS		DX-42-C	DX-60-8	DX-84
Nominal Bale Size	Width	42"	60"	84"
	Depth	30"	30"	48"
	Height	48"	48"	48"
Bale Weight Up To (OCC)		1,000 lbs	1,400 lbs	2,200 lbs
Cycle Time (Average)		58 sec	58 sec	50 sec
Cycle Time w/ Regen Option		N/A	N/A	N/A
Platen Force	Normal	100,500 lbs	100,500 lbs	113,100 lbs
	Max	120,600 lbs	120,600 lbs	124,400 lbs
Platen Face Pressure	Normal	82.5 psi	57.8 psi	28.1 psi
	Max	99 psi	69.4 psi	30.9 psi
Motor - 3 Phase	208/230/460 VAC	15 hp	15 hp	15 hp
Motor - 1 Phase	230 VAC	N/A	N/A	N/A
Pump Capacity		12 gpm	12 gpm	18 gpm
Hydraulic Reservoir	Capacity	33 gal	33 gal	50 gal
Hydraulic Cylinder	Bore Dia.	8"	8"	(two) 6"
	Stroke	54"	54"	60"
	Rod Dia.	5"	5"	3 1/2"
Operating Pressure	Normal	2,000 psi	2,000 psi	2,000 psi
	Max	2,400 psi	2,400 psi	2,200 psi

Cram-A-Lot DX Series DIMENSIONS	Overall Height Installed	Frame Height	Overall Width	Overall Depth with Door Closed	Overall Depth with Door Open	Loading Height	Feed Opening Height	Unit Weight
DX-42-C	12' 7"	8' 10"	4' 8"	3' 2"	6' 10"	57"	20 1/2"	5,400 lbs
DX-60-8	12' 7"	8' 10"	6' 2"	3' 1"	8' 3"	57"	20 1/2"	6,000 lbs
DX-84	15' 4"	8' 3"	8' 2"	4' 7"	11' 10"	57"	48"	11,500 lbs