



## Self Contained Compactor Specifications

(800) 678-7320

sales@jv.com

Cram-A-Lot SC Series SPECIFICATIONS		SC-T1 Models	SC-T2 Models	SC-T2-LP Low Profile Models	SC-02 Models	SC-02-LP Low Profile Models	SC-T2 Hydraulic Tailgate Models
<b>Charge Box Capacity</b>		1 cu yd	2 cu yd	2 cu yd	2 cu yd	2 cu yd	2 cu yd
<b>NWRA Rated Size</b>		0.75 cu yd	1.52 cu yd	1.14 cu yd	1.31 cu yd	1.03 cu yd	1.52 cu yd
<b>Theoretical Cycle Time</b>		28 sec	37 sec	37 sec	32 sec	32 sec	37 sec
<b>Total Force</b>	<b>Normal</b>	44,200 lbs	42,700 lbs	42,700 lbs	39,300 lbs	39,300 lbs	42,700 lbs
	<b>Maximum</b>	53,000 lbs	51,250 lbs	51,250 lbs	47,100 lbs	47,100 lbs	51,250 lbs
<b>Ram Face Pressure</b>	<b>Normal</b>	40.0 psi	24.5 psi	31.5 psi	22.6 psi	29.0 psi	24.5 psi
	<b>Maximum</b>	48.0 psi	29.5 psi	38.04 psi	27.1 psi	34.8 psi	29.5 psi
<b>Ram Face Dimensions</b>	<b>(W x H)</b>	48" x 23"	60" x 29"	60" x 23"	60" x 29"	60" x 23"	60" x 29"
<b>Ram Penetration</b>		6"	8"	8"	5.5"	5.5"	8"
<b>Motor - 3 Phase</b>	<b>208/230/460 VAC</b>	10 hp	10 hp	10 hp	10 hp	10 hp	10 hp
<b>Pump Capacity</b>		10.5 gpm	10.5 gpm	10.5 gpm	10.5 gpm	10.5 gpm	10.5 gpm
<b>Hydraulic Reservoir</b>	<b>Capacity</b>	22 gal	22 gal	22 gal	22 gal	22 gal	22 gal
<b>Hydraulic Cylinder</b>	<b>Bore Dia.</b>	(two) 4"	(two) 4"	(two) 4"	5"	5"	(two) 4"
	<b>Stroke</b>	26"	34"	34"	40"	40"	34"
	<b>Rod Dia.</b>	2"	2"	2"	2.5"	2.5"	2"
<b>Operating Pressure</b>	<b>Normal</b>	2000 psi	2000 psi	2000 psi	2000 psi	2000 psi	2000 psi
	<b>Maximum</b>	2400 psi	2400 psi	2400 psi	2400 psi	2400 psi	2400 psi

Cram-A-Lot SC Series DIMENSIONS	Overall Length	Packer Length	Clear Top (Length X Width)	Base Unit Weight	Base Unit Weight (LP Models)	Normal Container Capacity
SC-T1-10	13' 2"	60"	31"x 46"	6,500 lbs	N/A	10 cu yd
SC-T1-15	16' 6"	60"	31"x 46"	7,000 lbs	N/A	15 cu yd
SC-T1-20	19' 10"	60"	31"x 46"	7,500 lbs	N/A	20 cu yd
SC-T2-15	15'	71"	41"x 58"	8,900 lbs	8,770 lbs	15 cu yd
SC-T2-20	17' 4"	71"	41"x 58"	9,800 lbs	9,670 lbs	20 cu yd
SC-T2-25	19' 11"	71"	41"x 58"	10,000 lbs	9,870 lbs	25 cu yd
SC-T2-30	22' 1"	71"	41"x 58"	10,800 lbs	10,670 lbs	30 cu yd
SC-T2-34	23' 9"	71"	41"x 58"	10,900 lbs	10,770 lbs	34 cu yd
SC-T2-38	25' 10"	71"	41"x 58"	12,000 lbs	11,870 lbs	38 cu yd
SC-02-30	19'	90 1/2"	34"x 58"	9,860 lbs	9,680 lbs	20 cu yd
SC-02-25	21' 7"	90 1/2"	34"x 58"	10,100 lbs	9,920 lbs	25 cu yd
SC-02-30	23' 9"	90 1/2"	34"x 58"	10,800 lbs	10,630 lbs	30 cu yd
SC-02-34	25' 5"	90 1/2"	34"x 58"	10,900 lbs	10,720 lbs	34 cu yd
SC-T1-16-HTG	18'	60"	31"x 46"	8,000 lbs	N/A	16 cu yd
SC-T1-20-HTG	19' 8"	60"	31"x 46"	8,200 lbs	N/A	20 cu yd
SC-T1-25-HTG	23'	60"	31"x 46"	8,900 lbs	N/A	25 cu yd
SC-T2-20-HTG	17'	71"	41"x 58"	10,260 lbs	N/A	20 cu yd
SC-T2-25-HTG	19' 7"	71"	41"x 58"	10,900 lbs	N/A	25 cu yd
SC-T2-30-HTG	21' 9"	71"	41"x 58"	11,540 lbs	N/A	30 cu yd