

CRAM-A-LOT®

VB Baler Specifications and Dimensions

(800) 678-7320

sales@jv.com

Cram-A-Lot		VB-42-SR	VB-42-B	VB-46-LD	VB-60-B	VB-60-B-C	VB-60-B-LP	VB-60-H	VB-60-T	VB-60-X	VB-60-SR	VB-72-B	VB-72-B-LP	VB-72-H	VB-72-H-DC	VB-72-H-LP	VB-72-T	VB-72-X
VB Series																		
SPECIFICATIONS																		
Nominal Bale Size	Width	42"	42"	46"	60"	60"	60"	60"	60"	60"	60"	72"	72"	72"	72"	72"	72"	72"
	Depth	24"	30"	24"	30"	30"	30"	30"	30"	30"	30"	30"	30"	30"	42"	30"	30"	30"
	Height	28"	48	36"	48"	48"	38"	48"	48"	48"	30"	48"	38"	48"	51.5"	38"	48"	48"
Bale Weight Up To (OCC)		200 lbs	750 lbs	400 lbs	1,000 lbs	1,000 lbs	900 lbs	1,400 lbs	1,200 lbs	1,400 lbs	600 lbs	1,200 lbs	950 lbs	1,600 lbs	1,700 lbs	1,250 lbs	1400 lbs	1,600 lbs
Cycle Time (Average)		23 sec	57 sec	39 sec	56 sec	56 sec	45 sec	77 sec	56 sec	60 sec	43 sec	57 sec	45 sec	77 sec	77 sec	59 sec	56 sec	60 sec
Cycle Time w/ Regen Option		N/A	34 sec	N/A	33 sec	33 sec	27 sec	44 sec	33 sec	35 sec	N/A	34 sec	33 sec	44 sec	44 sec	35 sec	33 sec	35 sec
Platen Force		23,545 lbs	59,370 lbs	31,800 lbs	59,370 lbs	59,370 lbs	59,370 lbs	92,350 lbs	67,850 lbs	92,350 lbs	59,370 lbs	59,370 lbs	59,370 lbs	92,350 lbs	92,450 lbs	92,350 lbs	67,850 lbs	92,350 lbs
Platen Face Pressure		32 psi	48 psi	41 psi	48 psi	48 psi	48 psi	75 psi	55 psi	75 psi	48 psi	48 psi	48 psi	75 psi	43 psi	61 psi	45 psi	61 psi
Motor - 3 Phase	208/230/460 VAC	5hp	10hp	5 hp	10 hp	10 hp	10 hp	15 hp	15 hp	20 hp	10 hp	10 hp	10 hp	15 hp	15 hp	15 hp	15 hp	20 hp
Motor - 1 Phase	230 VAC	10hp	5hp	10hp	5hp	5hp	5hp	N/A	N/A	N/A	5 hp	5hp	5hp	N/A	N/A	N/A	N/A	N/A
Pump Capacity @ 1800 rpm		6 gpm	9 gpm	6 gpm	9 gpm	9 gpm	9 gpm	10.5 gpm	10.5 gpm	13.5 gpm	9 gpm	9 gpm	9 gpm	10.5 gpm	10.5 gpm	10.5 gpm	10.5 gpm	13.5 gpm
Hydraulic Reservoir	Capacity	11 gal	30 gal	11 gal	30 gal	30 gal	30 gal	30 gal	30 gal	30 gal	30 gal	30 gal	30 gal	30 gal	30 gal	30 gal	30 gal	30gal
Hydraulic Cylinder	Bore Dia.	(two) 3"	6"	4 1/2"	6"	6"	6"	7"	6"	7"	(two) 5"	6"	6"	7"	7"	7"	6"	7"
	Stroke	36"	44"	36"	44"	44"	34"	52"	52"	52"	23"	44"	34"	52"	52"	38"	52"	52"
	Rod Dia.	1.375"	3.5"	2.5"	3.5"	3.5"	3.5"	4"	4"	4"	3"	3.5"	3.5"	4"	4"	4"	4"	4"
Operating Pressure		(208-1800) - (230/460-2000) - (230,1PH-1650)	2100	2000	2100	2100	2100	2100	2400	2400	2100	2100	2100	2100	2400	2100	2400	2400

Cram-A-Lot	Feed Opening Height	Loading Height	Overall Width	Overall Depth with Door Closed	Overall Depth with Door Open	Frame Height	Overall Height Installed	Base Unit Weight
VB Series								
DIMENSIONS								
VB-42-SR	24"	34.75"	65.5"	36.5"	77.25"	70"	93"	2,550 lbs
VB-46-LD	24"	42"	68.5"	38.5"	82.5"	83"	117.5"	2,750 lbs
VB-42-B	24"	53"	65.75"	45.75"	85.5"	99"	141"	3,850 lbs
VB-60-B	24"	53"	83.5"	45.75"	103.75"	99"	141"	4,450 lbs
VB-60-B-C	24"	53"	83.5"	45.75"	103.75"	99"	141"	4,450 lbs
VB-60-B-LP	24"	43"	83.5"	45.75"	103.75"	89"	118.75"	4,100 lbs
VB-60-H	24"	53"	83.5"	45.75"	103.75"	99"	148.25"	5,000 lbs
VB-60-T	24"	53"	83.5"	45.75"	103.75"	99"	148.25"	4,800 lbs
VB-60-X	24"	53"	83.5"	45.75"	103.75"	99"	148.25"	5,050 lbs
VB-60-SR	24"	35.5"	83.5"	45.75"	103.75"	82"	94.5"	4200 lbs
VB-72-B	24"	53"	95.5"	45.75"	115.25"	99"	141"	4,850 lbs
VB-72-B-LP	24"	43"	95.5"	45.75"	115.25"	89"	118.75"	4520 lbs
VB-72-H	24"	53"	95.5"	45.75"	115.75"	99"	148.25"	5,450 lbs
VB-72-H-DC	24"	56.5"	95.5"	57.75"	127.75"	102.5"	151.75"	6,200 lbs
VB-72-H-LP	24"	43"	95.5"	45.75"	115.75"	89"	120"	5,000 lbs
VB-72-T	24"	53"	95.5"	45.75"	115.75"	99"	148.25"	5,200 lbs
VB-72-X	24"	53"	95.5"	45.75"	115.75"	99"	148.25"	5,500 lbs